

Description

Synthetic lubricant for DCT or DSG automatic transmission (double clutch transmission) which provides quicker and smoother gear changes and reduces fuel consumption. This oil has been designed for transmissions of the main light vehicle manufacturers, such as Volkswagen, Ford, and Mercedes-Benz.

Properties

- Excellent viscosity stability at both high and low temperatures, providing a smooth driving experience over a wide range of temperatures.
- Reduced vibration, improving driving comfort and extending the transmission's life.
- High resistance to oxidation and friction stability, increasing the oil drain interval.
- Improves the transmission's fuel economy compared to other automatic transmissions.
- Highly compatible with seals, avoiding lubricant loss due to leaks.

Quality levels

- MB 236.21 / 236.24 / 236.25
- VW TL 052 182 / TL 052 529
- FORD WSS-M2C-936-A
- PSA 9734.S2
- MITSUBISHI SSTF-I
- PORSCHE 999.917.080.00
- VOLVO 1161838 1161839
- BMW 83 222 148 578 / 83 222 148 579 / 83 220 440 214 / 83 222 147 477

Technical specifications

	UNIT	METHOD	VALUE
Color	0		Amber
Density at 15 °C	g/cm ³	ASTM D 4052	0,854
Viscosity at 100 °C	cSt	ASTM D445	6,9
Viscosity at 40 °C	cSt	ASTM D445	34
Viscosity at -40 °C	cP	ASTM D2983	17000
Viscosity index	-	ASTM D 2270	165
Flash point (COC)	°C	ASTM D 92	183
Pour point	°C	ASTM D 97	-48

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants

Edition 2, September 2019