

# ELITE EVOLUTION POWER 1 5W-30



AUTOMOTIVE

Lubricants

## Description

Very high performance "Fuel Economy" synthetic lubricant for light vehicles with incorporated exhaust treatment systems. Its studied formulation with very low ash content (Low SAPS) makes it appropriate for the latest engine technologies on the market that include particle filters and require the use of a ACEA C1 quality level oil. These devices contribute to lower particle emissions and better environmental protection. Designed specifically for Mazda, Ford, Mitsubishi, Jaguar and Land Rover vehicles.

## Properties

- Compatible with vehicles that include particle filters, preventing these devices from becoming blocked by excessive ash generation. It must be used only in vehicles for which manufacturers recommend the use of a ACEA C1 quality level product.
- The "Fuel Economy" properties mean that fuel can be saved under normal driving conditions; this contributes to decreasing levels of CO<sub>2</sub> emissions in the atmosphere,
- Its anti-friction additives help you to save on fuel while providing the protection against wear and tear that is required for high-performance engines.
- Excellent viscosity stability during the useful life of the oil thanks to the additives used to improve viscosity.

## Quality Levels

- ACEA C1

## Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			5W-30
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.849
Viscosity at 100 °C	cSt	ASTM D 445	10.2
Viscosity at 40 °C	cSt	ASTM D 445	55
Viscosity at -30 °C	cP	ASTM D 5293	6600 max.
Viscosity index	-	ASTM D 2270	176
Flash point, open cup	°C	ASTM D 92	205
Pour point	°C	ASTM D 97	-36 max.
T.B.N.	mg KOH/g	ASTM D 2896	6.6
Bosch Injector Shearing: Viscosity at 100 °C after shearing	cSt	CEC-L-14-93	9.3 min.
Sulphated ashes	% in weight	ASTM D 874	0.5 max.

A safety data sheet is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. September 2016.