

# CARTAGO GL-4+ 75W-80

GEARBOXES AND TRANSMISSIONS



## Lubricants

### Description

Synthetic lubricant for manual gearboxes and built-in differentials (transaxles) of passenger cars which require an API GL-4+ quality level and are subject to sudden changes in temperature. This oil has been specially designed to meet the lubricant requirements established by the main vehicle manufacturers (Peugeot, Citroën, Renault, General Motors, etc.) for their gearboxes and differentials.

### Properties

- High thermal stability and resistance to ageing, keeping it clean with a low level of deposit formation, which makes for a longer-lasting oil (increased time between changes).
- Offers a high level of protection against wear on gears and synchronizers, thus extending the transmission's lifespan.
- Allows for a smooth driving experience and silent gear switching.
- Capable of working at extreme operating temperatures as low as -40 °C, thanks to its excellent fluidity at low temperatures.

### Quality levels

- API GL-4/GL-5
- PSA: B71 2330

### Technical characteristics

	UNIT	METHOD	VALUE
Density at 15° C	g/ml	ASTM D 4052	0,860
Viscosity at 100° C	cSt	ASTM D 445	8,4
Viscosity at 40° C	cSt	ASTM D 445	45
Viscosity at -40° C	cP	ASTM D 2983	< 150.000
Viscosity index	-	ASTM D 2270	163
Flash point, V/A	°C	ASTM D 92	180
Freezing point	°C	ASTM D 97	-42

The above mentioned characteristics are typical values and should not be considered product specifications.

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. July 2019.