

# MOTO OFF ROAD 2T



MOTORCYCLE

## Lubricants

### Description

Synthetic lubricant oil for very high performance 2-stroke engines; it is mainly suitable for all top-level off-road specialities. This product has been conscientiously designed to ensure maximum engine protection against wear in the extreme conditions to which this type of motorbike is subjected. It is suitable for both premix and for injector lubrication systems.

### Properties

- Specially developed for use in conditions of high rotations, demonstrating superior capacity in off-road use.
- Excellent protection against wear and improved engine cleanliness guaranteed in conditions of extreme use.
- Its components prevent the formation of deposits, helping to keep the exhaust ports clean.
- It extends the engine's lifespan, preventing any sticking of the piston rings, sweating of spark plugs and the formation of carbonous residues.

### Quality Levels

- JASO M345 FD (Code 034RYL002)
- API TC
- Aprilia DFI
- ISO-L-EGD
- TISI

### Technical specifications

	UNIT	METHOD	VALUE
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.872
Viscosity at 100 °C	cSt	ASTM D 445	10
Viscosity at 40 °C	cSt	ASTM D 445	64
Viscosity index	-	ASTM D 2270	141
Flash point, open cup	° C	ASTM D 92	130
Pour point	° C	ASTM D 97	-33
T. B. N.	mg KOH/g	ASTM D 2896	2
Sulphated ashes	% in weight	ASTM D 874	0.1

A safety information file is available on request.

repsol.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 2 October 2010