

## Description

Lubricating oil for two-stroke outboard high performance engines. The formula with highly refined mineral bases and exclusive additives provides outstanding performance in jet skis, ensuring the best corrosion protection. Meets the requirements of the NMMA TC-W standard. The recommended dose blended with gasoline is 2%.

## Properties

- Protection against rust and corrosion of internal parts in marine environments.
- Segment sticking avoiding.
- Selected dispersing additives keep the engines and exhaust vents clean.
- Improving start-up and reducing friction.
- Protection against wear,
- Prevention of spark plug fouling and self-ignition.

## Quality Levels

- NMMA TC-W

## Technical specifications

	UNIT	METHOD	VALUE
Colour		Visual	Dark blue
Density at 15 °C	g/cm <sup>3</sup>	ASTM D 4052	0.875
Viscosity at 100 °C	cSt	ASTM D 445	7.71
Viscosity at 40 °C	cSt	ASTM D 445	47
Brookfield Viscosity at -25 °C	cP	ASTM D 5293	7500 max.
Viscosity index	-	ASTM D 2270	120 min.
Flash point, open cup	°C	ASTM D 92	115 min.
Pour point	°C	ASTM D 97	-24
T.B.N.	mg KOH/g	ASTM D 2896	6.5

A safety information file is available on request.

repsolpf.com  
+34 901 111 999

Technical data sheet for Lubricants. Revision 1. July 2016